

Xi-DESIGNER

Finish Collection



Xi-ACRYLSTAIN

DESCRIPTION

Xi-AcrylStain is an acrylic polymer based stain for use over multiple substrates including acrylic and cement finishes, coatings and Xi-Designer Finishes.

USAGE

Xi-AcrylStain is a specialized accent stain crafted for application over finishes, elevating the mottling effect and creating an aged, weathered appearance. Available in Xi-Standard colors.

For interior and exterior applications on properly prepared substrates.

PACKAGING

1 Gallon pail

COVERAGE

1200-1600 ft² per gallon

Coverages are approximate and will vary depending on application methods and environmental/surface conditions.

SHELF LIFE

12 months - stored off the ground, unopened, protected from moisture, extreme heat 90°F (32°C and direct sunlight.

SURFACE PREPARATION

Clean all surface by removing dirt dust and debris prior to application.

The surface must be clean, dry, sound and free of contaminants such as form release agents, paint, dust, oil, mildew and efflorescence.

Ambient conditions, substrate and the product itself must be at a minimum of 40°F during application and at least 48 hours

Cement and gypsum plaster: cure for a minimum of seven days

Concrete and masonry: Curing or a minimum of 28 days.

MIXING

Stir very carefully until just mixed and color is dispersed. Do not add water.

APPLICATION

Xi-Designer Finishes are each unique to the product, application methods and substrate and the final appearance is solely dependent upon the applicators skill and techniques.

The contractor must be qualified in the installation of the product.

A written acceptance of a sample mock-up of the final product using the application method and tools to be used in the actual installation is required between the owner and the contractor.

DRY STAINING

Start with a completely dry surface

1. Moisten the wall slightly with a spray bottle.
2. Apply Xi-AcrylStain using a moistened sponge or cloth

WET STAINING

1. While the finish coat is slightly wet, moisten the wall very lightly with a spray bottle.
2. Immediately apply Xi-AcrylStain using a spray bottle or sponge.
3. Using a stainless steel trowel, Trowel the stain into the finish using decorative strokes in multiple directions.

CLEAN UP

Clean tools and equipment with water immediately and during use. Dried material can only be removed mechanically.

CAUTIONS / LIMITATIONS

In no way is FACADESXi responsible for color variations or color correctness after the product has been applied, or for application or substrates out of accordance with the manufacturers' specifications, building code, associations standards or guidelines.

Provide supplemental heat and protection from moisture as needed.

Use only clean tools and materials to avoid contamination. Only use cleaners approved by FacadesXi.

Avoid application in direct sunlight.

SAFETY

**KEEP OUT OF REACH OF CHILDREN.
FOR PROFESSIONAL USE ONLY.
DO NOT ALLOW PRODUCT TO FREEZE.
VOC < 10 GRAMS PER LITER.**

The instructions for use and application and warnings have been prepared in good faith based on the information available at the time of publication.

All instructions are intended to provide product users with the proper guidelines for use and application under normal working and environmental conditions. Because each project and user is different, FACADESXi cannot be held responsible for any consequences of variations in conditions or for unforeseen conditions when using this product.

For the most up to date information go to:
facadesxi.com.

WARNINGS

Use of this product can expose you to Crystalline Silica, a chemical that has been known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information:
P65Warnings.ca.gov

INHALATION

This product is considered an irritant if proper precautions aren't followed. Use a NIOSH approved respirator mask and adequate ventilation when using the product. Avoid overexposure. Open windows and doors to confined areas during the application and drying process. Ensure fresh airflow is available. Leave the area of application immediately if you experience watery eyes, dizziness, or a headache.

SKIN CONTACT

Do not get product in your eyes or on your skin. Wash hands thoroughly after use.

EYE CONTACT

Rinse eyes thoroughly with water for several minutes. Remove contact lenses then continue to rinse.

DO NOT TAKE INTERNALLY

Immediately contact the Poison Control Center if swallowed. Store product in its original container sealed tightly after use.

EXPOSURE TO LEAD

Scraping sand or old paint chips may result in toxic lead exposure. For more information, call the National Lead Information Hotline at **1-800-424-LEAD** or visit online at: epa.gov/lead.

PLEASE NOTE

The most current Safety Data Sheet and Product Data Sheet can be found on our website for more information on product handling