

Xi-DESIGNER

Finish Collection



Xi-DRAPPLED EARTH

DESCRIPTION

Xi-Drappled Earth is an acrylic Trowel-applied plaster finish with colored granules.

USAGE

Xi-Drappled Earth creates the look of masonry, concrete, or plaster with a subtle weathered appearance or an aged Old World distressed plaster finish.

Available in standard or custom color and can be enriched with staining and polishing techniques.

For interior and exterior applications on properly prepared substrates.

SUBSTRATES

- Concrete
- Stucco
- CMU
- Masonry
- Interior gypsum board
- EIFS

“Wet” areas require a sealer.

FEATURES / BENEFITS

- Economical option to natural plaster
- Varying aesthetics
- Easy to apply
- Extremely Durable

PACKAGING

1 and 5 Gallon pail.

COVERAGE

30-40 ft² per gallon (two coats).

Coverages are approximate and will vary depending on application methods and environmental/surface conditions.

SHELF LIFE

12 months - stored off the ground, unopened, protected from moisture, extreme heat 90°F (32°C and direct sunlight.

SURFACE PREPARATION

Clean all surface by removing dirt dust and debris prior to application.

The surface must be clean, dry, sound and free of contaminants such as form release agents, paint, dust, oil, mildew and efflorescence.

Ambient conditions, substrate and the product itself must be at a minimum of 40°F during application and at least 48 hours

The surface must be smooth and level, Xi-Drappled Earth is a thin product and cannot correct any imperfections in the substrate.

Cement and gypsum plaster: Cure for a minimum of seven days

Concrete and masonry: Curing or a minimum of 28 days.

New Drywall: Gypsum Association GA-214, Level 3 finish

Priming is required over painted substrates and recommended for all other surfaces.

Xi-Drappled Earth

