

NOTES:

- 1. For full assembly options, materials and placement of materials refer to the specific FacadesXi System specifications
- 2. System must be sealed at all penetrations. It is recommended to install penetrations before the Classing and sealing at the WaterShield layer.
- 3. Attach penetrations to structural member.

DISCLAIMER: FACADESXi details are recommendations that should be used for guidance only. In the may be equivalent means of installation that are not shown in FACADESXi assembly details.All FACADESXi products shall be installed in accordance with FACADESXi product datasheets and all applicable building codes and industry standard practices. The design, engineering and final details incorporating any FACADESXi product are the sole responsibility of the project design professional.FACADESXi is not responsible for determining the acceptability and/or applicability of any FACADESXi product or detail for any specific project or condition.IFACADESXi isclaims all liability for improper installation, workmanship,or design by a third-party.EXCEPT FOR ANY EXPRESS REPRESENTATIONS AND WARRANTIES BY FACADESXi, ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COMPLIANCE WITH LAWS OR GOVERNMENT RULES OR REGULATIONS APPLICABLE TO THE PROJECT, ARE HEREBY DISCLAIMED. FACADESXi's website should always be consulted for the latest version of any details and/or product information. Contact FACADESXi for any technical assistance.