

Xi-DESIGNER

Finish Collection



Xi-AGED SILK

DESCRIPTION

Xi-Aged Silk is a worn/old world plaster with an array of textures, ranging from sleek to rugged in design. Installed in standard plaster application methods.

USAGE

Xi-Aged Silk creates a natural leather or suede look with understated mottling.

Available in standard or custom color and can be enriched with staining and polishing techniques.

SUBSTRATES

- Concrete
- Stucco
- CMU
- Masonry
- Interior gypsum board
- EIFS

“Wet” areas require a sealer.

FEATURES / BENEFITS

- Economical option to natural plaster
- Varying aesthetics
- Easy to apply
- Extremely Durable

PACKAGING

1 and 5 Gallon pail.

COVERAGE

36-42 ft² per gallon (two coats).

Coverages are approximate and will vary depending on application methods and environmental/surface conditions.

SHELF LIFE

12 months – stored off the ground, unopened, protected from moisture, extreme heat 90°F (32°C and direct sunlight.

SURFACE PREPARATION

Clean all surface by removing dirt dust and debris prior to application.

The surface must be clean, dry, sound and free of contaminants such as form release agents, paint, dust, oil, mildew and efflorescence.

Ambient conditions, substrate and the product itself must be at a minimum of 40°F during application and at least 48 hours

The surface must be smooth and level, Xi-Aged Silk is a thin product and cannot correct any imperfections in the substrate.

Cement and gypsum plaster: Cure for a minimum of seven days

Concrete and masonry: Curing or a minimum of 28 days.

New Drywall: Gypsum Association GA-214, Level 3 finish

Priming is required over painted substrates and recommended for all other surfaces.

Xi-Aged Silk

